



GTO Trans LD 80W90

Description	<p>This universal gear oil is based on high quality solvent refined base oils and special EP-additives to obtain the following properties:</p> <ul style="list-style-type: none">- an excellent activity against high temperature load- excellent activity against wear, corrosion and foam- a low pour point- very special EP-properties- widely usable												
Application	<p>This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.</p>												
Performance Level	<p>Meets the requirements of API GL-3/GL-4/GL-5/MT-1 MIL-L-2105/MIL-PRF-2105E, SAE J2360 DAF MAN 341 Typ Z2/MAN 342 Typ M2 Scania STO 1:0 ZF TE-ML 02B/04G/05A/07A/12L/12M ZF TE-ML 16B/16C/17H/19B/21A MB 235.0 Mack GO-J Iveco</p>												
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,900</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>146,40</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>15,20</td></tr><tr><td>Viscosity Index</td><td>105</td></tr><tr><td>Flash Point COC, °C</td><td>200</td></tr><tr><td>Pour Point, °C</td><td>-30</td></tr></table>	Density at 15 °C, kg/l	0,900	Viscosity 40 °C, mm ² /s	146,40	Viscosity 100 °C, mm ² /s	15,20	Viscosity Index	105	Flash Point COC, °C	200	Pour Point, °C	-30
Density at 15 °C, kg/l	0,900												
Viscosity 40 °C, mm ² /s	146,40												
Viscosity 100 °C, mm ² /s	15,20												
Viscosity Index	105												
Flash Point COC, °C	200												
Pour Point, °C	-30												