



## Gto Trans ATF D2

### Description

A very high graded automatic transmission fluid formulated with solvent refined and synthetic base oils and a number of selected additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

### Application

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIIH fluid is required.

### Performance Level

Allison C4/TES-389  
Cat TO-2  
Ford Mercon/M2C138-CJ/166-H  
GM Dexron IID/IIE/IIIF/IIIG/IIIH  
MAN 339 Typ Z1/V1  
MB 236.1/236.5/236.6/236.7/236.9  
Voith 55.6335 (G607)  
Volvo 97341  
ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

### Typicals

Density at 15 °C, kg/l	0,851	
Viscosity 40 °C, mm <sup>2</sup> /s		37,70
Viscosity 100 °C, mm <sup>2</sup> /s		7,60
Viscosity Index		175
Flash Point COC, °C		210
Pour Point, °C		-51

4/26/2018

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.