



## GTO Trans 80w90 GL-4

<b>Description</b>	<p>This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high-quality solvent refined base oils and special EP-additives to obtain the following properties:</p> <ul style="list-style-type: none"><li>- a good resistance against oxidation</li><li>- good rust-preventing, anti-corrosion and foam inhibiting properties</li><li>- a low pourpoint</li><li>- good Extreme Pressure (EP) properties</li></ul>												
<b>Application</b>	<p>This multi purpose gear oil should be used in hypoid differentials, gearboxes and other transmissions, for which an EP-transmission oil is advised.</p>												
<b>Specifications</b>	<p>Performance level API GL-4</p>												
<b>Typicals</b>	<table><tr><td>Density at 15 °C, kg/l</td><td>0,881</td></tr><tr><td>Viscosity 40 °C, mm<sup>2</sup>/s</td><td>150,50</td></tr><tr><td>Viscosity 100 °C, mm<sup>2</sup>/s</td><td>15,20</td></tr><tr><td>Viscosity Index</td><td>102</td></tr><tr><td>Flash Point COC, °C</td><td>214</td></tr><tr><td>Pour Point, °C</td><td>-27</td></tr></table>	Density at 15 °C, kg/l	0,881	Viscosity 40 °C, mm <sup>2</sup> /s	150,50	Viscosity 100 °C, mm <sup>2</sup> /s	15,20	Viscosity Index	102	Flash Point COC, °C	214	Pour Point, °C	-27
Density at 15 °C, kg/l	0,881												
Viscosity 40 °C, mm <sup>2</sup> /s	150,50												
Viscosity 100 °C, mm <sup>2</sup> /s	15,20												
Viscosity Index	102												
Flash Point COC, °C	214												
Pour Point, °C	-27												